


PRODUCT RANGE 2025



IMIT
IMIT CONTROL SYSTEM

IMIT: leader in thermoregulation for over a hundred years.

History

Since 1917, at IMIT we have always discussed solutions. We began with electromechanics, becoming the leaders in temperature regulation. We are constantly at the forefront of technology and have invested all the experience gained in millions of products installed in the best home appliances and in the most diverse appliances all over the world. While we have upheld the same principle since the dawn of our company: solutions, first of all.

Philosophy

The IMIT CONTROL SYSTEM philosophy has decided to take up the challenge: new products, absolute quality, immediate processes, with a careful and above all a concrete look at renewable energies.

There is no innovation without solid skills to start with.

Our products are the best that thermoregulation can offer: functionality and simplicity of use, integration and professionalism, design and energy saving.

Product quality

Using the skills acquired by the company, employees, suppliers and customers is the only one way to obtain a quality standard adapted to new technologies and the pressing demand for renewal.

The constant goal of the IMIT CONTROL SYSTEM is quality in all stages of production, as well as proposing the ideal solutions, guaranteeing the highest quality and respecting the deadlines agreed with customers.

Customer service

An excellent degree of efficiency may also be verified through the competence and organisation of customer service where the customer is able to find expert and reliable personnel.

The IMIT CONTROL SYSTEM brings together the know-how of our long experience both in the electromechanical field and in the electronic field, including our customised industrial and civil solutions to make customised equipment for any need.

Our presence

Our IMIT CONTROL SYSTEM reaches over 1,000 customers all over the world. We have sales networks available in our different specialised market areas both for the Industry and the Distribution sectors.

We are also able to guarantee a qualified pre-sales and after-sales service, both for mechanical and electronic equipment.

www.imit.it



Products

CLIMATE ADJUSTMENT

Room thermostats	p.06
Programmable thermostats	p.07
Built-in thermostats and Programmable Thermostats	p.12
Fan-Coil regulators	p.14



INDUSTRIAL COMPONENTS


Capillary thermoregulators	p.16
Capillary safety limiters	p.18
Thermometers, Pressure gauges, Manometers	p.19

THERMAL CENTRAL

Boxed regulation and safety thermostats	p.24
---	------

SYSTEMS FOR RENEWABLE ENERGY SOURCES

Electronic regulators for fireplace, thermo-stove, thermo-heater ..	p.30
Hydraulic interfacing modules	p.31
Accessories for biomass systems	p.34



CLIMATE ADJUSTMENT

Room thermostats


Programmable thermostats

Built-in thermostats and Programmable thermostats

Fan-Coil regulators



TA3 MECHANICAL WALL-MOUNTED THERMOSTAT




TA3 is a mechanical wall thermostat with saturated steam expansion tank, ideal for regulating home or office temperature. It is available in LED versions, without LED, ON / OFF (to turn off the thermostat without turning the knob), Summer / Winter (to connect and regulate the air conditioning or heating system). This thermostat also offers the possibility to limit or block the set temperature, through the installation of an optional switch under the cover.

Electrical contact capacity = 16(2,5) A / 250 Vac
 Regulation range = 5°÷30°C
 Differential = 1K
 Insulation class = II
 Protection rating = IP20
 Max. tolerance temperature = 50°C
 Connection = 2 wires
 Output = changeover switches
 Operating mode: On/Off or Summer/Winter
 System: heating/air conditioning
 Certifications: CE, ENEC03, EAC

Code	Article	Description	Pack.
546070	TA3	3-contact thermostat	20
546030	TA3-A	3-contact thermostat-LED indicator light	20
546010	TA3-B	3-contact thermostat - LED indicator light - ON / OFF switch	20
546230	TA3-C	2-contact thermostat - LED indicator - summer winter switch	20
000071	SWITCH	Switch for knob lock	a.r.
004095	BOTTOM PIECES	Bottom pieces for TA3 in black	a.r.

TA5 MECHANICAL WALL-MOUNTED THERMOSTAT



TA5 is a mechanical wall thermostat with saturated steam expansion tank, ideal for regulating home or office temperature. It is available in LED versions, without LED, ON / OFF (to turn off the thermostat without turning the knob), Summer / Winter (to connect and regulate the air conditioning or heating system). This thermostat also offers the possibility to limit or block the set temperature, through the installation of an optional switch under the cover. Thanks to the new external ergonomic knob, temperature regulation is simple and accessible to everyone.


Electrical contact capacity = 16(2,5) A / 250 Vac
 Regulation range = 5°÷30°C
 Differential = 1K
 Insulation class = II
 Protection rating = IP20
 Max. tolerance temperature = 50°C
 Connection = 2 wires
 Output = changeover switches
 Operating mode: On/Off or Summer/Winter
 System: heating/air conditioning
 Certifications: CE, ENEC03, EAC

Code	Article	Description	Pack.
546770	TA5	3-contact thermostat	20
546730	TA5-A	3-contact thermostat-LED indicator light	20
546710	TA5-B	3-contact thermostat - LED indicator light - ON / OFF switch	20
546750	TA5-C	2-contact thermostat - LED indicator - summer winter switch	20
000071	SWITCH	Switch for knob lock	a.r.
004095	BOTTOM PIECES	Bottom pieces for TA5 in black	a.r.

SILVER TA S DIGITAL ROOM WALL-MOUNTED THERMOSTAT



Also available in radio version




SILVER TA S is a digital room thermostat with TPI algorithm, ideal for regulating heating or cooling. The backlit LCD display clearly shows the detected room temperature, set temperature, active operating mode, status icons and flat battery warning. The external knob makes temperature regulation even more immediate. Includes the Antifreeze function and allows temperature calibration with a range of ±8°C.

Operating current: 3V DC (2 AAA alkaline batteries)
 Relay NO Switching current: 2A/30VDC (Resistive load) 2A/250VAC (Resistive load)
 Temperature measurement accuracy: 0.1°C
 Operating sensitivity: 0.5°C
 Operating temperature range: 5°÷30°C
 Battery life: 1 year (2 x AAA)
 Operating temperature: -10°÷50°C
 Storage temperature: -20°÷60°C

Code	Article	Description	Pack.
578811	SILVER TA S	Digital room thermostat	5
578816	SILVER TA/RF S	Radio digital room thermostat (433 Mhz)	5

CHRONOMIX S DAILY WALL-MOUNTED PROGRAMMABLE THERMOSTAT




CHRONOMIX-S is an electronic daily programmable thermostat that is extremely simple and intuitive. Through a switch clock you may choose which one of the two levels of temperature to activate at a certain time. It is ideal for regulating home or office temperature, through the two knobs that manage comfort or reduced temperature, perfect for the regulation of different temperatures during the day and night or during your absence. Easy to set up, but highly technological, thanks to its TPI operation that allows exploiting thermal inertia in every type of environment, guaranteeing absolute comfort and energy and economic savings and an ErP contribution of 4%.

Electrical contact capacity = 5(1) A / 250 Vac
 Temperature range = 10°÷30°C
 Differential = 0.5 K
 Insulation class = II
 Protection rating = IP20
 Max. room temperature = 50°C
 Power supply = 2 x 1.5V-LR6 AA batteries
 Operating mode: Manual / Automatic
 Heating system
 Form of control: TPI (optional)
 Certifications = CE, ENEC03

Code	Article	Description	Pack.
578180	CHRONOMIX-S	Daily Programmable Thermostat with switch clock	5

TECHNO DUO

DAILY WALL-MOUNTED CHRONOTHERMOSTAT



TECHNO DUO is a programmable electronic daily switch thermostat. The LCD display (backlit blue) shows the room temperature, set time or temperature, daily programming, active mode of operation and low battery indicator. The automatic program can be set to half an hour or an hour. It memorises the anti-freeze threshold and two temperature levels (comfort and reduced, day and night), and regulates both the air conditioning and heating systems, through the three modes of operation: Manual/Automatic/Anti-freeze. The TPI function (optional) allows exploiting thermal inertia in every type of environment, guaranteeing absolute comfort, and energy and economic savings and an ErP contribution of 4%. Ideal for those who want constant programming during the week or for those who have difficulty with technology.

Electrical contact capacity = 5(1) A / 250 Vac
 Regulation range = 5°±35°C
 N° of settable temperatures = 2
 Time slots = 0.5 h e 1 h
 Differential = 0,2 K
 Thermometer resolution = 0,1°C
 Thermometer precision = ±0,3°C
 Max. room temperature = 50°C
 Insulation class = II
 Protection rating = IP20
 Options = 12h/24h clock and °C/°F selection
 Operating mode: Manual/Automatic/Anti-freeze
 System: heating/air conditioning
 Form of control: TPI (optional)
 Certifications = CE, ENEC03


Code	Article	Description	Pack.
578160	TECHNO DUO	Daily chronothermostat with switch clock and LCD display	5

SILVER CR-W

WEEKLY WALL-MOUNTED PROGRAMMABLE THERMOSTAT



Also available in radio version



SILVER CR-W is a programmable digital weekly chronothermostat. The backlit LCD display shows the detected temperature, time and set temperature, active operating mode and the time programming in use. It offers 3 different preset programs (Comfort, Economy and Holiday) as well as the possibility of setting a customized manual or weekly program, on two temperature levels (comfort and reduced). It includes the TPI modulation function, allowing to reach the ErP IV class, also present the antifreeze function, allows the temperature calibration with a range of ±8°C.


Power supply: 3 Vdc (2 x AAA alkaline batteries)
 Switching current: 2A (230 Vac) Relay NO
 Temperature measurement accuracy: 0.1°C
 Differential: 0.3°C.
 Operating temperature range: 5°±30°C
 Battery life: 1 year (2 x AAA)
 Operating temperature: -10°±50°C
 Storage temperature: -20°±60°C

Code	Article	Description	Pack.
578827	SILVER CR-W	Weekly Programmable Thermostat	5
578829	SILVER CR-W RF	Weekly radio Programmable Thermostat	5

ORION WIFI

WEEKLY WALL-MOUNTED PROGRAMMABLE THERMOSTAT

New in 2025



Power supply = 230 V ac
 Type of regulation = Selectable during installation
 ErP class = IV (-2%) in ON/OFF mode with TPI
 ErP class I (-1%) in traditional ON/OFF mode
 Type of system = Heating/Air conditioning
 Operating modes = Manual / Automatic / Antifreeze
 Type of programming = Weekly on 2 temperature levels
 Minimum programming time slot = 30 minutes
 Maximum contact capacity = 5A (1A) 250Vac
 Temperature regulation range = 5.0°C -35.0°C
 Tolerance 0.3 K
 Differential = Adjustable between 0.1 and 2.0 K (Standard 0.2 K)
 Backlit display with adjustable intensity
 Web-App compatible with systems: Android-iOS-Alexa-Google
 Certifications = CE

The Orion WIFI chronothermostat is the ideal solution for those who want precise and convenient control of the home temperature. Thanks to the WIFI connection, you can manage the heating and cooling of the home directly from your smartphone or PC, wherever you are.

Key Features:

- Remote Control: Adjust your home temperature via the Web App independent of the various updates of iOS and Android systems.
- Weekly Programming: Set custom heating programs for each day of the week.
- Compatibility: Works with most heating and cooling systems.
- Modern Design: Backlit display (with adjustable intensity) and elegant design that adapts to any environment.

Advantages:

- Comfort: keeps your home at the ideal temperature at all times.
- Efficiency: reduces energy consumption.
- Ease of use: simple installation and intuitive use thanks to the user-friendly app.
- Updates: automatic reception of software for new features and improvements; in addition to automatic synchronization of the time and day of the week.
- it is possible to configure more than one chronothermostat in the same home, especially if you have different areas or floors that you want to control separately.
- Configuration via the Web-App to add and configure each chronothermostat.
- Individual programming: set customized heating/cooling programs for each area based on your needs.
- Configuring multiple chronothermostats allows you to have more precise control and optimize comfort and energy efficiency in every part of the home.

Note:

- You can use the chronothermostat even without a WIFI connection, but with some limitations. Without WIFI, you can still:
- Manually adjust the temperature: using the controls on the device itself.
- Set heating programs: directly on the chronothermostat.


Warning: for the appliance to work, you need a WiFi router (fixed or mobile network), a PC (Windows or Os) and/or a smartphone (Os or Android).

Code	Article	Description	Pack.
578842	ORION WI FI	ORION WI FI Weekly Programmable Thermostat Wi Fi	5

ORION DAY DAILY WALL-MOUNTED PROGRAMMABLE THERMOSTAT



Also available in radio version




ORION DAY is a digital daily Programmable Thermostat, also available in radio version. Thanks to the TPI logic, it exploits the thermal inertia of any type of environment, for absolute comfort, energy savings and an ErP IV contribution up to 2%. It combines simplicity of programming with energy saving, with 2 temperatures that can be set in 30-minute steps. Thanks to the large backlit LCD display, it's possible to visualize the detected temperature, time or set temperature, and operating modes: Auto (Comfort-Eco)/Manual/Antifreeze (Off). The 24 hourly micro-pushbuttons and the other controls are easily accessible, but protected by a clean cover which makes them suitable for any installation environment. It is ideal for those who have different habits depending on the time of day or have environments that they use at different times of the day.

Power supply = 2x1.5V AAA type alkaline batteries (lasting > 1 year)
 Type of regulation = Selectable during installation
 ErP class = IV (-2%) in ON/OFF mode with TPI
 ErP class = I (-1%) in traditional ON/OFF mode
 Type of system = Heating/Air Conditioning
 Operating modes = Manual / Automatic / Antifreeze
 Type of Programming = Daily on 2 temperature levels
 Minimum programming time slot = 30 minutes
 Contact maximum rating = 5A (1A) 250Vac (ON/OFF mode only)
 Temperature setting range = 5.0-35.0 °C
 Tolerance +/- 0.3K
 Differential = Adjustable between 0.1 and 2.0K (Standard 0.2K)
 Options = Clock format 12/24H
 Backlit display
 Maximum ambient temperature = 50°C
 Storage temperature = -25°C ÷ 60°C
 Insulation class = Type II (Double insulation)
 Degree of protection = IP20
 Approvals = CE

Code	Article	Description	Pack.
578830	ORION DAY	ORION DAY Daily On/Off	5
578831	ORION DAY/RF	ORION DAY/RF Daily On/Off Radio (868.2 Mhz)	5

ORION DAY OT DAILY WALL-MOUNTED PROGRAMMABLE THERMOSTAT OPENTHERM IN CLASS V



ORION DAY OT is a Class V ErP digital daily Programmable Thermostat, which uses the OpenTherm communication protocol. It combines simplicity of programming with energy savings up to 4% on each bill, with 2 temperatures that can be set in 30-minute steps. Thanks to the large LCD display, it is possible to visualize the detected temperature, time or set temperature and operating mode: Auto (Comfort-Eco)/Manual/Antifreeze (Off). The 24 hourly micro-pushbuttons and the other controls are easily accessible, but protected by a clean cover which makes them suitable for any installation environment. It is ideal for those who have different habits depending on the time of day or have environments that they use at different times of the day.


Power supply = via BUS cable from Opentherm boiler
 ErP class = V (- 4%) in OpenTherm mode
 Type of system = Heating/Air Conditioning
 Operating modes = Manual / Automatic / Antifreeze
 Type of Programming = Daily on 2 temperature levels
 Minimum programmable time slot = 30 minutes
 Contact maximum rating = 5A (1A) 250Vac (ON/OFF mode only)
 Temperature setting range = 5.0-35.0°C
 Differential = Adjustable between 0.1 and 2.0K (Standard 0.2K)
 Options = Clock format 12/24H
 Backlit display = only if combined with OPENTHERM boilers
 Compatible
 Storage temperature = -25°C ÷ 60°C
 Approvals = CE, OPENTHERM

Code	Article	Description	Pack.
578835	ORION DAY/OT	ORION DAY/OT Daily OT	5

ORION WEEK WEEKLY WALL-MOUNTED PROGRAMMABLE THERMOSTAT



Also available in radio version




ORION WEEK is a weekly digital Programmable Thermostat, also available in radio version. Thanks to the TPI logic, it exploits the thermal inertia of any type of environment, for absolute comfort, energy savings and an ErP IV contribution up to 2%. It combines simplicity of programming with energy saving, with 2 temperatures that can be set in 30-minute steps. Thanks to the large backlit LCD display, it is possible to visualize the detected temperature, time or set temperature, and operating modes: Auto (Comfort-Eco)/Manual/Antifreeze (Off). The 24 hourly micro-pushbuttons and the other controls are easily accessible, but protected by a clean cover which makes them suitable for any installation environment. It is ideal for those who have different habits depending on the day of the week or have environments that they use at different times of the day.

Power supply = 2x1.5V AAA type alkaline batteries (Duration > 1 year)
 Type of regulation = Selectable during installation
 ErP class = IV (-2%) in ON/OFF mode with TPI
 ErP class = I (-1%) in traditional ON/OFF mode
 Type of system = Heating/Air Conditioning
 Operating modes = Manual / Automatic / Antifreeze
 Type of Programming = Weekly on 2 temperature levels
 Minimum programming time slot = 30 minutes
 Contact maximum rating = 5A (1A) 250Vac (ON/OFF mode only)
 Temperature setting range = 5.0°C -35.0°C
 0.3K tolerance
 Differential = Adjustable between 0.1 and 2.0K (Standard 0.2K)
 Options = Clock format 12/24H
 Backlit display
 Maximum ambient temperature = 50°C
 Storage temperature = -25°C ÷ 60°C
 Approvals = CE

Code	Articolo	Description	Pack.
578840	ORION WEEK	ORION WEEK Weekly On/Off	5
578841	ORION WEEK/RF	ORION WEEK/RF Weekly On/Off Radio (868.2 Mhz)	5

ORION WEEK OT WEEKLY WALL-MOUNTED PROGRAMMABLE THERMOSTAT OPENTHERM IN CLASS V



ORION WEEK OT is a Class V ErP digital weekly Programmable Thermostat, which uses the OpenTherm communication protocol. It combines simplicity of programming with energy savings up to 4% on each bill, with 2 temperatures that can be set in 30-minute steps. Thanks to the large LCD display, it is possible to visualize the temperature detected, the time or temperature set, the active day of the week and the operating mode: Auto (Comfort-Eco)/Manual/Antifreeze (Off). The 24 hourly micro-pushbuttons and the other controls are easily accessible, but protected by a clean cover which makes them suitable for any installation environment. It is ideal for those who have different habits depending on the day of the week or have environments that they use at different times of the day.

Power supply = via BUS cable from Opentherm boiler
 ErP class = V (- 4%) in OpenTherm mode
 Type of system = Heating/Air Conditioning
 Operating modes = Manual / Automatic / Antifreeze
 Type of Programming = Weekly on 2 temperature levels
 Minimum programmable time slot = 30 minutes
 Contact maximum rating = 5A (1A) 250Vac (ON/OFF mode only)
 Temperature setting range = 5.0°C 35.0 °C
 Differential = Adjustable between 0.1 and 2.0K (Standard 0.2K)
 Options = Clock format 12/24H
 Backlit display = only if combined with OpenTherm boilers compatible
 Storage temperature = -25°C ÷ 60°C
 Approvals = CE, OPENTHERM

Code	Article	Description	Pack.
578870	ORION WEEK/OT	ORION WEEK/OT Weekly OT	5

TAE/503S BUILT-IN ELECTRONIC ROOM THERMOSTAT



TAE/503S is a DIN503 built-in room thermostat, ideal for regulating the temperature of your home or office. It can manage both the air conditioning and heating systems and the three operating modes Summer/Winter/Antifreeze are very simple to set, thanks to the practical knob for regulating the temperature. An LED signals low batteries. It is ideal for small rooms, when temperature programming is not necessary or to manage temperature variations in delimited areas. The package includes 4 interchangeable frames for use with the majority of aesthetic switch plates on the market and an additional front panel + knob that allow you to vary the color (white/black) of the device.

Electrical contact capacity = 8(5) A / 250 Vac
 Regulation range = 5°÷30°C
 Power supply = 2 x 1.5V-LR6 AA batteries
 Max. room temperature = 50°C
 Insulation class = II
 Protection rating = IP40
 Operating mode: Summer/Winter/Anti-freeze
 System: heating/air conditioning
 Certifications = CE

Code	Article	Description	Pack.
560065	TAE/503S	Built-in room thermostat, AA battery power supply	10

DUO/503S BUILT-IN DAILY PROGRAMMABLE THERMOSTAT



DUO / 503S is a built-in programmable DIN503 thermostat with switches. It is ideal for regulating the temperature of the home or office and can manage both the air conditioning system and heating systems. Thanks to the backlit LCD display you can display the measured temperature, set temperature, time and the active mode of operation: Manual/Automatic/Anti-freeze. Time programming at 1 hour intervals is carried out via the practical mechanical switches. It is ideal for those who want to have simple and constant programming during the week or for those who have difficulty with technology. The package includes 4 interchangeable frames for use with most aesthetic switch plates on the market and an additional front panel that allow you to vary the color (white/black) of the device.

Electrical contact capacity = 8(5) A / 250 Vac
 Regulation range = 5°÷35°C
 Power supply = 2 x 1.5V-LR6 AA batteries
 N° of settable temperatures = 2
 Time slots = 1 h
 Thermometer precision = ±0,3°C
 Max. room temperature = 50°C
 Insulation class = II
 Protection rating = IP40
 Operating mode: Manual/Automatic/Anti-freeze
 System: heating/air conditioning
 Certifications = CE

Code	Article	Description	Pack.
560075	DUO/503S	Daily built-in Programmable Thermostat, AA battery power supply	10

CRD/503S BUILT-IN WEEKLY PROGRAMMABLE THERMOSTAT



CRD/503S is a programmable built-in weekly programmable thermostat DIN503 with three programmable temperatures at intervals of 1 hour. It is ideal for managing the temperature of your home or office and can regulate both the air conditioning and heating systems. Thanks to the backlit LCD display you can display the measured temperature, set temperature, time, active day and the operating mode: Manual/Automatic/Anti-freeze. It is ideal for those with different habits depending on the day of the week or for those who have environments that they use at different times of the day. The package includes 4 interchangeable frames for use with most aesthetic switch plates on the market and an additional front panel that allows you to vary the color (white/black) of the device.

Electrical contact capacity = 8(5) A / 250 Vac
 Regulation range = 5°÷35°C
 Power supply = 2 x 1.5V-LR6 AA batteries
 N° of settable temperatures = 3
 Time slots = 1 h
 Thermometer precision = ±0,3°C
 Max. room temperature = 50°C
 Insulation class = II
 Protection rating = IP40
 Operating mode: Manual/Automatic/Anti-freeze
 System: heating/air conditioning
 Certifications = CE

Code	Article	Description	Pack.
560085	CRD/503S	Weekly built-in Programmable Thermostat, AA battery power supply	10

ACCESSORIES FOR BUILT-IN THERMOSTATS



Kit of aesthetic-plates for built-in DIN503, glossy black colour.


Code	Article	Description	Pack.
557022	PLATES KIT	Set of 5 glossy black aesthetic-plates	a.r.

FRAME COMPATIBILITY WITH PLATES

FRAME A COMPATIBILITY	FRAME B2 COMPATIBILITY	FRAME C COMPATIBILITY	FRAME D COMPATIBILITY
<p>IMIT Bticino Light, Light tech, Living international, Matrix. Vimar Idea, Idea Rondò. Gewiss Playbus, Playbus young. Ave Banquise, Sistema 45, Noir. Siemens Delta futura Legrand Ergo, Cross, Vela.</p>	<p>Bticino Luna, Axolute, Living now. Vimar Plana, Eikon, Eikon Evo. Gewiss Chorus. Master Modo, Mix.</p>	<p>Bticino Living Light air, Axolute Air.</p>	<p>Ave sistema 44. Vimar Archè. EC Elettrocantali Prestige, Life.</p>

FAN TA3

MECHANICAL REGULATOR FOR FAN-COIL



FAN TA3 is an electromechanical steam expansion regulator for fan-coils, radiators and fan convectors. It is ideal for regulating home or office temperature in its two modes of operation: Summer/Winter (to activate the air conditioning or heating functions). It is also equipped with a mechanical three-position switch for regulating fan speeds and to control the hot/cold valve.

Power supply = 230 Vac
 Regulation range = 7°÷30°C
 Differential = 1 K
 Thermostat contact capacity = 16(2,5) A / 250 Vac
 Selector switch capacity = 10(2) A / 250 Vac
 Output = changeover switches
 Installation = wall
 Operating mode: Summer/Winter/Anti-freeze
 System: fan-coil/radiators/fan convectors
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
548501	FAN TA3 SE	Room thermostat for FAN-COIL E/I	20

FAN/503S

FAN-COIL REGULATOR



The new FAN / 503S is a DIN 503 built-in fan-coil regulator, with the main functions of the previous FAN 503, for the management and control of 2 solenoid valves (hot and cold) for 2 or 4 pipe systems. The product has been equipped with a new backlit display and a version designed to control the inverter motors, with consequent energy savings.

Water probe: NTC 10K @25°C ±1% with double insulation
 230V fan version outputs:
 5 Relays (3 motor speeds + 2 solenoid valves)
 0-10V brushless motor version outputs: 2 Relays (2 solenoid valves) / 0-10V modulating fan
 Electrical contact capacity: 3 (1) A - 250VAC
 Protection rating: IP 20 (with product installed)
 Insulation class:
 Pollution degree: 2
 Software class: A
 Thermal gradient: 1K/15min.
 Maximum operating temperature: 50°C
 Humidity limits: 20% .. 80% RH (non condensing)
 Storage temperature: 0÷60°C
 Operating mode: summer / winter: (heating / air conditioning)
 Assembly: in standard 3-module flush-mounting box (DIN503)
 Certifications: CE

Power supply: 230V~/50Hz (+10% -15%)
 Power consumption: 3VA
 Temperature regulation range: 5°C÷35°C
 Minimum temperature adjustment range: 0,1°C
 Room temperature display: 0÷40°C (resolution 0,1°C)
 Differential: settable: (0,4K factory setting)
 Ambient probe on board: NTC 100K @25°C ±1%

Code	Article	Description	Pack.
578380	FAN/503S	Electronic built-in regulator for fan-coil with 3-speed fan motor @ 230V	5
578385	FAN/503S 0-10V	Electronic built-in regulator for fan-coil with 0-10V modulating brushless fan motor (inverter)	5

ACCESSORIES FOR FAN/503S

Aesthetic-plates and frame for built-in DIN503 for Bticino Living International, Gewiss Playbus and Playbus Young, Vimar Idea and Rondò, IMIT. Glossy black colour.


Code	Article	Description	Pack.
076410	FRAME 503	Frame for DIN 503 box	a.r.

INDUSTRIAL COMPONENTS

- Capillary thermoregulators
- Capillary safety limiters
- Thermometers, Pressure gauges, Manometers



TR2 CAPILLARY REGULATION THERMOSTAT



TR2 is a liquid expansion capillary thermostat, unipolar, with changeover switches, particularly suitable for automatic temperature regulation for appliances in the field of civil and industrial heating, air conditioning and household appliances such as boilers, washing machines, dish-washers, etc.

Electrical contact capacity = NC 16(6) / A 250 Vac
 Switches = changeover
 Max. head temperature = 85°C
 Min. capillary curvature radius = 5 mm
 Connection = via faston 6,3x0,8
 Certifications = CE, ENEC03, EAC, UL

Code	Article	Adjustable temperature °C	Capillary length mm	Bulb size mm	Pack.
540010	TR2 INAIL	0/+90	1000	6.5*95	100
540355	TR2 INAIL	0/+90	1500 PVC	6.5*95	100
541307	TR2 INAIL CUTTING SCREW	0/+90	1500	6.5*95	100
540043	TR2	-30/+35	1000	6*215	100
540030	TR2	0/+40	1000	9.5*92	100
540160	TR2	0/+120	1000	6.5*95	100
540673	TR2	0/+120	1500	7*90 M14*1	100
540140	TR2	+70/+210	1000	5*125	100
540020	TR2	+50/+300	1000	3.5*195	100


KIT TR2 CAPILLARY REGULATION THERMOSTAT



KIT TR2 includes a TR2 with adjustable temperature range 0 to 90°C, capillary 1500 PVC, INAIL certified, complete with knob and dial.

Code	Article	Description	Pack.
5R0359	KIT TR2	Single package with TR2, knob and dial	10

TRZ 2-STAGE CAPILLARY REGULATION THERMOSTAT



TRZ is a capillary thermostat with liquid expansion probe and 2-stage switch, unipolar, with switching contacts, particularly suitable for automatic temperature regulation for applications in civil and industrial heating, air conditioning and household appliances such as radiators electric, boilers, washing machines, dishwashers, etc.

Electrical contact capacity = 15 (2,5) A / 250 Vac
 Switches = changeover
 Max. head temperature = 80°C
 Capillary length = 1500 mm PVC
 Min. capillary curvature radius = 5 mm
 Connection = via faston
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
544024	TRZ	2-stage thermostat: 1st stage 40/78°C, second stage 47/85°C	50


ACCESSORIES FOR TR2 AND TRZ



Knobs are designed according to the need for regulation and the support dials.

Code	Article	Description	Pack.
556301	KNOB	Knob 0/90°C	20
556302	KNOB	Knob with an arrow	20
556303	KNOB	Knob 0/120°C	20
556313	KNOB	Knob 70/210°C	20
556326	KNOB	Knob 50/300°C	20
556343	KNOB	Knob 0/40°C	20
556360	KNOB	Knob -30/+30°C	20
556501	DIAL	Chrome dial	20
556503	DIAL	Black dial	20
556978	SPRING	Spring for knob	20
556979	STILL	Knob latch	20

LS1/LS3 CAPILLARY SECURITY LIMITERS



LS1 / LS3 is a capillary thermostat with a liquid expansion probe, unipolar, with safety temperature limiter with manual or automatic reset and with positive safety in case of capillary breakage. It is particularly suitable for boilers, heating systems and in all those appliances where it is necessary not to exceed a maximum set temperature.

Switches = interrupted due to temperature increase
 Max. head temperature = 85°C
 Copper bulb = 125°C
 Copper bulb = Ø 6,5 x 95 mm
 Min. capillary curvature radius = 5 mm
 Certifications = CE, ENEC03, EAC, UL

Code	Article	Temperature°C	Capillary length mm	Electrical contact capacity	Reset	Pack.
541510	LS1	+90/+110	1000	16(6) A/ 250 V~	MANUAL	100
541550	LS1 INAIL	+100	1000	16(6) A/ 250 V~	MANUAL	100
541563	LS1 INAIL	+100	1500 PVC	16(6) A/ 250 V~	MANUAL	100
541750	LS3	+100	1000	100mv 0.3A cc	AUTOMATIC	100

KIT LS1 CAPILLARY SECURITY LIMITERS



KIT LS1 includes a LS1 100° C with capillary 1500 PVC, INAIL certified, with manual reset, complete with cap and stop.

Code	Article	Description	Pack.
541569	KIT LS1	Single package with LS1, Cap and stop	30

THERMOMETERS CAPILLARY



Range of thermometers with liquid expansion probe, particularly suitable for appliance on boilers, refrigerators, catering appliances, home appliances. The thermometers are available with different measurement ranges, shapes, designs and customisable colours.

Casing = plastic
 Max. body temperature = 70°C
 Certifications = CE, EAC

Code	Article	Description	Pack.
010247	THERMOMETER	Circular thermometer 0/120°C, Ø 52mm, Capillary 1500mm PVC, black casing, white typeface, black screen	50
060107	THERMOMETER	Circular thermometer 0/120°C, Ø 37mm, Capillary 1500mm PVC, black casing, black typeface, white screen	50
013451	THERMOMETER	Square thermometer 0/120°C, Frame 54*54mm Built-in Ø52mm, Capillary 1500mm PVC, black casing, white typeface, black screen	50
042101	THERMOMETER	Square thermometer 0/120°C, Frame 48*48mm, Capillary 1000mm PVC, black casing, white typeface, black screen	50
021968	THERMOMETER	Rectangular thermometer 10/105°C, 58 *25mm, capillary 1500mm PVC. Black casing, black typeface, white screen	50
010836	THERMOMETER	Circular thermometer 50/350°C, Ø 52mm, Capillary 1000mm, black casing, white typeface, black screen	50

MANOMETERS CAPILLARY



Range of manometers with capillary connection, particularly suitable for appliance on boilers, fireplaces, heaters and home appliances. Pressure gauges are available with different measuring ranges, shapes, designs and customisable colours.

Working range = 0/6 bar
 Casing = plastic
 Max. body temperature = 70°C
 Certifications = CE, EAC

Code	Article	Description	Pack.
035553	MANOMETER	Circular manometer 0/6 bar, Ø 52mm, Capillary 1500mm PVC, black casing, white typeface, black screen	50
066226	MANOMETER	Circular manometer 0/4 bar, Ø 37mm, Capillary 1500mm PVC, G1/4" connection, black casing, black typeface, white screen	50
036660	MANOMETER	Square manometer 0/6 bar, Frame 55*55mm, Built-in Ø52mm, Capillary 1500mm PVC, M14*1 fitting, black casing, white typeface, black screen	50

THERMOMANOMETER CAPILLARY



Range of liquid expansion thermomanometers and connection for manometer. Particularly suitable for appliance on boilers, fireplaces, heaters and home appliances. Available in a round version with different measuring ranges and colours (customisable typeface and dials).

Working range = 0/120°C - 0/6 bar
Casing = plastic
Max. body temperature = 70°C
Certifications = CE, EAC

Code	Article	Description	Pack.
030646	THERMOMANOMETER	Thermomanometer 0/120°C 0/6 bar, Ø 52mm, Capillary 1500 PVC, M14*1 fitting, black casing, white typeface, black screen	50

POCKETS AND ACCESSORIES

FOR TR2 AND LS THERMOSTATS, THEMOMETERS, PRESSURE GAUGES, MANOMETERS

Pockets for the immersion of TR2 and LS thermostats, fittings and tie-rods for coupling to different types of connection and check valves.

Code	Article	Description	Pack.
555001	POCKET	Pocket Ø 7*8 mm - L=50 mm - G1/2"	20
555002	POCKET	Pocket Ø 7*8 mm - L=100 mm - G1/2"	20
555004	POCKET	Pocket Ø 7*8 mm - L=120 mm - G1/2"	20
555012	POCKET	Pocket Ø 15*16 mm - L=100 mm contour - G1/2"	20
555014	POCKET	Pocket Ø 15*16 mm - L=120 mm contour - G1/2"	20
555027	POCKET	Pocket Ø 7*8 mm - L=200 mm - G1/2"	20
555034	POCKET	Pocket Ø 15*16 mm - L=100 mm - G1/2"	20
555035	POCKET	Pocket Ø 15*16 mm - L=120 mm - G1/2"	20
556554	SPRING	Pocket spring 15*16	a.r.
556557	SPRING	External spring	a.r.
556559	SPRING	Pocket spring 7*8	a.r.
501576	BRACKET	Bracket for thermometers and manometers Ø 52mm	a.r.
501578	LATCH	Latch for M4 tie rod	a.r.
501579	LATCH	Latch for M6 tie rod	a.r.
001565	RETENTION VALVE	M14*1 - G1/2" valve	a.r.
001566	RETENTION VALVE	G1/4"- G1/2" valve	a.r.
001567	RETENTION VALVE	G1/4" - G1/4" valve	a.r.
557205	ADAPTER	G1/4" manometer adapter	a.r.
557206	ADAPTER	M14*1 manometer adapter	a.r.

MGR PLUG-IN THERMOSTAT



Plug-in thermostat particularly suitable for electric boilers

Code	Article	Description	Pack.
554760	MGR	Plug-in thermostat 10/80°C Boom L = 280mm	50

ARMORED COPPER RESISTANCE



Copper resistors particularly suitable for boilers


Code	Article	Description	Pack.
550670	RESISTANCE	Threaded copper resistance G1 ¼ " 1200W 230V	50
550680	RESISTANCE	Threaded copper resistance G1 ¼ " 1500W 230V	50
550200	RESISTANCE	Threaded copper resistance G1 ¼ " 2000W 230V	50

BC42 BIMETALLIC THERMOSTAT



Contact thermostat particularly suitable for fan convectors and fan heaters.

Code	Article	Description	Pack.
557500	BC42	Contact micro-switch, closing temperature 42 °C ± 3.5 °C - opening temperature 32 °C ± 3.5 °C. - Connection clamps and stainless steel fixing spring.	10




THERMAL CENTRAL

Boxed regulation and safety thermostats



TC2 REGULATION THERMOSTAT IN IP40 CONTAINER




TC2 is a boxed immersion thermostat with liquid expansion, unipolar, with changeover switches, complete with a watertight protection pocket. The thermostat normally applied on delivery piping is particularly suitable for the automatic regulation of boilers, pumps and other various appliances. It is also available in a capillary version.

Electrical contact capacity = 10(2,5) A / 250 Vac
 Switches = interrupted due to temperature increase or exchange
 Max. head temperature = 80°C
 Max. bulb temperature = 125°C
 Thermal gradient = 1°K/min
 Protection rating = IP40
 Certifications = CE, ENEC03, DIN, PED, EAC

Code	Article	Description	Pack.
5R2470	TC2 INAIL	Adjustable thermostat 0/90°C, Pocket G1/2" L=100	10
542425	TC2 INAIL	Adjustable thermostat 0/90°C, Pocket G1/2" L=200	10
542441	TC2	Adjustable thermostat 40/210°C, Pocket G1/2" L=100	10
542440	TC2	Adjustable thermostat 40/210°C, Pocket G1/2" L=200	10
542562	TC2 INAIL	Adjustable thermostat 0/90°C, Capillary L=1000	10

TLSC REGULATION AND SAFETY BI-THERMOSTAT IN IP40 CONTAINER




TLSC is a double boxed immersion thermostat, with liquid expansion probes, unipolar, temperature regulator and temperature limiter, fail-safe for capillary breakage, complete with watertight protection pocket. Particularly suitable for appliances where temperature control and safety is required.

Electrical contact capacity = 10 (2,5) A / 250 Vac
 Switches = interrupted due to temperature increase or exchange
 Max. head temperature = 80°C
 Max. bulb temperature = 125°C
 Thermal gradient = 1°K/min
 Protection rating = IP40
 Certifications = CE, ENEC03, DIN, PED, EAC

Code	Article	Description	Pack.
5R2714	TLSC	Bi-thermostat regulation 0/90°C, safety 90/110°C, Pocket G1/2" L=100	5
5R2731	TLSC INAIL	Bi-thermostat regulation 0/90°C, safety 100°C, Pocket G1/2" L=100	5

LSC1 SAFETY LIMITER IN IP40 CONTAINER




LSC1 is a boxed immersion thermostat, with liquid expansion probe, unipolar, safety temperature limiter with manual reset, fail-safe for capillary breakage, complete with watertight protection pocket. Useful in appliances where safety is required due to the temperature increase.

Electrical contact capacity = 10(2,5) A / 250 Vac
 Switches = interrupted due to temperature increase
 Thermal gradient = 1°K/min
 Max. head temperature = 80°C
 Max. bulb temperature = 125°C
 Protection rating = IP40
 Certifications = CE, ENEC03, DIN, PED, EAC

Code	Article	Description	Pack.
543010	LSC1	Safety thermostat 90/110°C, Pocket G1/2" L=120 Manual reset	10
543031	LSC1 INAIL	Safety thermostat 100°C, Pocket G1/2" L=100 Manual reset	10
543151	LSC1	Safety thermostat 90/110°C, Perforated pocket L=230 Manual reset	20

BRC CONTACT THERMOSTAT




BRC is a bimetallic boxed thermostat, unipolar, with interrupted or changeover switches. Especially suitable for measuring and regulating temperature.

Differential = 8±3K
 Electrical contact capacity = 16(2,5) A / 250 Vac
 Thermal gradient = 1°K/min.
 Max. head temperature = 80°C
 Protection rating = IP20
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
5R5610	BRC	Bimetallic contact thermostat 20/90°C	20
5R5860	BRC	Bimetallic contact thermostat 20/90°C internal regulation	20

TCR REGULATION THERMOSTAT IN IP40 CONTAINER





TCR is a liquid expansion boxed thermostat, unipolar, with interrupted or changeover switches, for contact appliances. Particularly suitable for measuring and regulating temperature.

Differential = $10 \pm 3K$
 Max. head temperature = $55^{\circ}C$
 Protection rating = IP40
 Electrical contact capacity = $10(2,5) A / 250 Vac$
 Protection rating = IP40
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
543451	TCR	Liquid expansion contact thermostat 20/90°C	20

TTCA REGULATION BI-THERMOSTAT IN IP40 CONTAINER




TTCA is a double regulation thermostat for burner control (internal regulation) and fan start or stop (external regulation).

Electrical contact capacity = $10(2,5) A / 250 Vac$
 Adjustable temperature FAN = $0^{\circ}/60^{\circ}C$
 Internal adjustable temperature LIM = $30^{\circ}/120^{\circ}C$
 Protection rating = IP40
 Max. head temperature = $80^{\circ}C$
 Max. bulb temperature = $150^{\circ}C$
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
542860	TTCA	Ext. regulation thermostat $0/60^{\circ}C$, int. regulation $30/120^{\circ}C$, with perforated pocket $16*120mm$	5
542870	TTCA	Ext. regulation thermostat $0/60^{\circ}C$, int. regulation $30/120^{\circ}C$, with perforated pocket $16*230mm$	5
542873	TTCA	Ext. regulation thermostat $0/60^{\circ}C$, int. regulation $30/120^{\circ}C$, with $12*280mm$ boom pocket	5
542833	TTCA	Ext./int. regulation thermostat $0/90^{\circ}C$, with $G \frac{1}{2}$ " pocket $15*16*100mm$	5

TCS ADJUSTABLE SAFETY LIMITER IN IP40 CONTAINER




TCS adjustable safety limiter in Ip40 container TCS is a liquid expansion boxed safety thermostat, unipolar, with interrupted contacts. Especially suitable for appliances and for securing temperature.

Temperature limiter pre-regulation = $60^{\circ}C$
 Regulation range = $40^{\circ}/70^{\circ}C$
 Tolerance = $0-10K$
 Manual reset
 Reset temperature = $-25K \pm 8K$ range
 Max. head temperature = $55^{\circ}C$
 Electrical contact capacity = C-1: $0,5 A / 250 Vac$ C-2: $10(2,5) A / 250 Vac$
 Protection rating = IP40
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
543454	TCS	Safety liquid expansion contact thermostat $40/70^{\circ}C$	20

ETR REGULATION THERMOSTAT IN IP54 CONTAINER




ETR is an adjustable boxed thermostat for controlling temperature in various appliances, especially suitable for environments with a high degree of pollution. Protection rating IP54.

Differential = from 3 to $6^{\circ}C$
 Electrical contact capacity = $16(2,5) A / 250 Vac$
 Max. operating temperature = $65^{\circ}C$
 Protection rating = IP54
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
544400	ETR	Regulation thermostat $0/55^{\circ}C$ with joined nickel-plated bulb $9.5*92mm$	5
544401	ETR	Regulation thermostat $-35/+35^{\circ}C$ with joined nickel-plated bulb $9.5*92mm$	5
544402	ETR	Regulation thermostat $-35/+35^{\circ}C$ with $2000mm$ nickel-plated capillary	5

ERT/TA ROOM THERMOSTAT IN IP40-IP54 CONTAINER



ERT/TA is an adjustable boxed thermostat for controlling the temperature in various appliances, particularly suitable for environments with a high degree of pollution.

Differential = from 1.5 to 3°C
 Electrical contact capacity = 16(2,5) A / 250 Vac
 Max. operating temperature = 65°C
 Protection rating = IP54 / IP40
 Certifications = CE, ENEC03, EAC

Code	Article	Description	Pack.
544404	ERT	Thermostat, watertight 0/40°C, joined IP54 Spiral sensor	5
544405	ERT	Thermostat, watertight -5/+35°C, joined IP54 Spiral sensor	5
544610	TA	Thermostat, watertight 0/40°C, joined IP40 Spiral sensor	20

SYSTEMS FOR RENEWABLE ENERGY SOURCES

- Electronic regulators for fireplace, thermo-stove, thermo-heater
- Hydraulic interfacing modules
- Accessories for biomass systems



FIRE WATER HID SIMPLE

REGULATOR FOR HYDRO FIREPLACES/
KITCHENS AND THERMOSTUPS



FIRE WATER HID SIMPLE is a DIN503 built-in electronic regulator for fireplaces, compact, with an attractive design adaptable to each installation environment. It can control a water heating system circulator thanks to its microprocessor logic. It can also control the manual activation of a "grill" rotisserie motor. Complete with probe immersion, electrical box and black aesthetic plate.

Power supply = 230 Vac / 50 Hz
Max. absorbed power = 3,2 W
Electrical contact capacity = 3(1) A 250 Vac
Usable probes = NTC 10 K @ 25°C
Temperature display = 3,0÷99,9 °C
Resolution = 0,1°C
Operating room temperature = 0÷50°C
Insulation class (with installed device) = II
Protection rating (with installed device) = IP20
Certifications = CE, ENEC03

Code	Article	Description	Pack.
578190	FIRE WATER HID SIMPLE	Electronic built-in regulator for thermo-fireplaces, 1 circulation pump and "grill" outlet system	5
058007	PROBE	Spare NTC 10K probe	a.r.

FIRE WATER HID

REGULATOR FOR HYDRO FIREPLACES/KITCHENS AND THERMOSTUPS






FIRE WATER HID is a built-in DIN503 electronic regulator for fireplaces, compact, with an attractive design, adaptable to every installation environment. Through its microprocessor logic, it manages the circulator of a water heating system and another circulator in the primary circuit (thermo-fireplace/thermo-heater), a 3-way diverter valve, a flow switch or flow meter, an auxiliary changeover switch. The controller has up to 3 inputs, usable for temperature probes. It also includes 7 different pre-set operating logics depending on the system in question. Complete with immersion probe, electrical box and black aesthetic plate.

Power supply = 230 Vac / 50 Hz
Max. absorbed power = 3,2 W
Electrical contact capacity = 3(1) A 250 Vac
Usable probes = NTC 10 K @ 25°C
Temperature display = 3,0÷99,9°C
Resolution = 0,1°C
Operating room temperature = 0÷50°C
Insulation class (with installed device) = II
Protection rating (with installed device) = IP20
Certifications = CE, ENEC03

Code	Article	Description	Pack.
578257	FIRE WATER HID	Electronic built-in regulator for thermo-fireplaces, 2-circulator system, 3-way diverter valve, flow switch, AUX switch, 3 temperature probe inputs	5
058007	PROBE	Spare NTC 10K probe	5

WATERLINK WLS4/WTL4

HYDRAULIC INTERFACE MODULE





WATERLINK WLS4 / WTL4 is a hydraulic separation module between two heat generators powered by different energy sources.

An appliance example is that of combining a thermo-fireplace (or a thermo-heater) and a gas boiler. When handling heat produced by biomass, the module disables the gas boiler and send hot water to the domestic heating system, enabling the boiler only as needed. It is available with a 34-plate and 40-plate exchanger, for 1 or 2 circulators, with or without cover casing and control unit.

Supply voltage = 230 V / 50 Hz
Max. absorbed power = 100 W
Water temperature probe = NTC 1 %
Operating water temperature = 0/95°C
Max. water probe temperature = 150°C
Working room temperature = 0/50°C
Storage temperature = 0/60°C
Max. fluid pressure = 3 bar
Protection rating = IPX4D
Certifications = CE

Code	Article	Description	Pack.
561595	WATERLINK WLS4 (1 pump, 34 plates)	Hydraulic module (heating only), with 1 circulator, 34-plate heat exchanger, without cover casing.	a.r.
561596	WATERLINK WLS4 (2 pumps, 34 plates)	Hydraulic module (heating only), with 2 circulators, 34-plate heat exchanger, without cover casing.	a.r.
561597	WALTERLINK WLS4 (1 pump, 40 plates)	Hydraulic module (heating only), with 1 circulator, 40-plate exchanger, without cover casing.	a.r.
561598	WATERLINK WLS4 (2 pumps, 40 plates)	Hydraulic module (heating only), with 2 circulators, 40-plate exchanger, without cover casing.	a.r.
561552	WATERLINK WTL4 (1 pump, 34 plates)	Hydraulic module (heating only), with 1 circulator, 34-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.
561553	WATERLINK WTL4 (2 pumps, 34 plates)	Hydraulic module (heating only), with 2 circulators, 34-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.
561560	WATERLINK WTL4 (2 pumps, 40 plates)	Hydraulic module (heating only), with 2 circulators, 40-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.
561599	WLS4 cover	Compact ERP waterlink cover kit	a.r.

WATERLINK WTL6 HYDRAULIC INTERFACE MODULE




WATERLINK WTL6 is a hydraulic separation module between two heat generators powered by different energy sources. The most typical appliance is that between a thermo-fireplace (or a thermo-heater) and a gas boiler. When handling heat produced by the biomass source, the module disables the traditional boiler and activates the 3-way valve to send hot water to the domestic heating system. Otherwise the 3-way valve is not enabled, allowing the gas boiler to meet the required heating needs.

Supply voltage = 230 V / 50 Hz
 Max. absorbed power = 100 W
 Water temperature probe = NTC 1%
 Operating water temperature = 0/95°C
 Max. water probe temperature = 150°C
 Working room temperature = 0/50°C
 Storage temperature = 0/60°C
 Max. fluid pressure = 3 bar
 Protection rating = IPX4D
 Certifications = CE

Code	Article	Description	Pack.
561554	WATERLINK WTL6 (1 pump)	Hydraulic module (heating only), with 1 circulator, 1 x 3-way diverter valve, 1 x 34-plate exchanger, complete with cover and FIRE WATER HID control unit.	a.r.
561555	WATERLINK WTL6 (2 pumps)	Hydraulic module (heating only), with 2 circulators, 1 x 3-way diverter valve, 1 x 34-plate exchanger, complete with cover and FIRE WATER HID control unit.	a.r.

WATERWARM HYDRAULIC INTERFACE MODULE




WATERWARM is a compact hydraulic kit, combined with a pellet stove or a thermo-fireplace, which allows the production of domestic hot water and water for heating. It includes a delivery/return group, a brazed exchanger with 20 plates, a diverter valve, a flow switch, an ErP circulator with degasser and built-in drain (only for code 561551) and a pre-wired electrical junction box. Includes white painted cover casing.

Supply voltage = 230 V / 50 Hz
 Max. absorbed power = 50 W
 Operating water temperature = 0/95°C
 Working room temperature = 0/50°C
 Storage temperature = 0/60°C
 Max. heating fluid pressure = 3 bar
 Max. fluid pressure ACS = 6 bar
 Protection rating = IPX4D
 Certifications = CE

Code	Article	Description	Pack.
561550	WATERWARM GRH (without circulator)	DHW production and heating hydraulic module, without circulator	a.r.
561551	WATERWARM GRH (with circulator)	DHW production and heating hydraulic module, with circulator	a.r.

WATERCOMBI WTC7 HYDRAULIC INTERFACE MODULE





WATERCOMBI WTC7 is a hydraulic separation module between two heat generators powered by different energy sources, with the production of domestic hot water. The most typical appliance is that of the combination between a thermo-fireplace (or a thermo-heater) and a boiler. When handling heat produced by the biomass source, the module disables the traditional boiler and sends hot water to the domestic heating system or directly to the user in the event of requesting domestic hot water. Otherwise, it allows the gas boiler to meet the heating demand and produce domestic hot water.

Supply voltage = 230 V / 50 Hz
 Max. absorbed power = 100 W
 Water temperature probe = NTC 1%
 Operating water temperature = 0/95°C
 Max. water probe temperature = 150°C
 Working room temperature = 0/50°C
 Storage temperature = 0/60°C
 Max. heating fluid pressure = 3 bar
 Max. fluid pressure ACS = 6 bar
 Protection rating = IPX4D
 Certifications = CE

Code	Article	Description	Pack.
561556	WATERCOMBI WTC7 (1 pump)	Hydraulic heating and DHW module, with 1 circulator, 1 x 3-way diverter valve, 1 flow switch, 1 x 30-plate exchanger, 1 x 14-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.
561557	WATERLINK WTC7 (2 pumps)	Hydraulic heating and DHW module, with 2 circulators, 1 x 3-way diverter valve, 1 flow switch, 1 x 30-plate exchanger, 1 x 14-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.

WATERPUFFER WTP5 HYDRAULIC INTERFACE MODULE



WATERPUFFER WTP5 is a hydraulic separation and integration module between hydraulic circuits with open or closed vessel, powered by different energy sources. The most typical appliance is that of the combination between a thermo-fireplace (or a thermo-heater) and a traditional boiler for the domestic management of heating and hot water with a storage tank. When handling heat produced by biomass, the module disables the gas boiler and send hot water to the domestic heating system or the storage tank, letting the boiler work only as needed.

Supply voltage = 230V / 50Hz
 Max. absorbed power = 100 W
 Water temperature probe = NTC 1%
 Operating water temperature = 95°C
 Max. water probe temperature = 150°C
 Working room temperature = 0/50°C
 Storage temperature = 0/60°C
 Max. fluid pressure = 3 bar
 Protection rating = IPX4D
 Certifications = CE

Code	Article	Description	Pack.
561561	WATERPUFFER WTP5 (1 pump)	Hydraulic module for heating and storage, with 1 circulator, 1 x 3-way diverter valve, 1 x 34-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.
561562	WATERPUFFER WTP5 (2 pumps)	Hydraulic module for heating and storage, with 2 circulators, 1 x 3 way diverter valve, 1 x 34-plate exchanger, complete with cover casing and FIRE WATER HID control unit.	a.r.

KIT GRH COMPONENTS FOR DOMESTIC HOT WATER PRODUCTION



Hydraulic units and accessories that make up the domestic hot water production kit.

Code	Article	Description	Pack.
561326	GRH DELIVERY UNIT	Hydraulic brass delivery unit, complete with diverter valve and safety valve	a.r.
561327	GRH ACTUATOR	Electric actuator for GRH 230Vac diverter valve	a.r.
561328	GRH RETURN UNIT (quick coupling)	Return brass hydraulic unit, complete with flow switch, loading tap, filter and flow limiter, quick connection for circulator	a.r.
561369	GRH RETURN UNIT (G3 / 4" attack)	Return brass hydraulic unit, complete with flow switch, loading tap, filter and flow limiter, G3/4" fitting	a.r.
561370	GRH FLOW SWITCH	Flow switch, threaded cap and Reed sensor	a.r.

CIRCULATORS ErP ACCESSORIES AND SPARE PARTS FOR BIOMASS PLANTS



Circulation pumps suitable for domestic installations.

Code	Article	Description	Pack.
083889	HYDRAULIC MODULAR CIRCULATOR	Wilo Para ErP circulator G1 connections, center distance 130 mm	a.r.

BRAZED HEAT EXCHANGERS ACCESSORIES AND SPARE PARTS FOR BIOMASS PLANTS



Heat exchangers for hydraulic units with different powers depending on the characteristics of the system.

Code	Article	Description	Pack.
07A708	GRH EXCHANGER	20-plate heat exchanger with switches	a.r.
076198	HYDRAULIC MODULE EXCHANGER	40-plate heat exchanger for 4*G3/4"M	a.r.
078891	HYDRAULIC MODULE EXCHANGER	34-plate heat exchanger 4*G3/4"M	a.r.
07A700	HYDRAULIC MODULE EXCHANGER	30-plate heat exchanger for 4*G3/4"M	a.r.
07A701	HYDRAULIC MODULE EXCHANGER	14-plate heat exchanger 4*G3/4"M	a.r.

DIVERTER VALVES ACCESSORIES AND SPARE PARTS FOR BIOMASS PLANTS




Diverter valves for hydraulic heating and DHW systems.

Code	Article	Description	Pack.
561351	DIVERTER VALVE	Motorised DN20 diverter valve G3/4"M, vertical body, 230Vac servo motor, 0/90° in 30"	a.r.
561352	DIVERTER VALVE	Motorised DN20 diverter valve 1"M, horizontal body, 230Vac servomotor, 0/90° in 30"	a.r.


CUSTOM ELECTRONICS

CUSTOMISED EQUIPMENT AND SYSTEMS FOR THE OEM SECTOR




Imit specialises in the development and production of customised electronic equipment and systems for the regulation and control of temperature, pressure and humidity in boilers, pellet stoves and chimney flues, heat pumps, fan-coils, electric radiators, home appliances for community applications, electro-medical sterilisers and in general for industrial contexts of various types.

The lengthy operating experience in the field of civil and industrial thermoregulation with the use of both electromechanical and electronic technology allows us to propose innovative, integrated and competitive solutions characterised by high quality standards and in compliance with the international regulations.



Design



A design team defines, in co-design or autonomously, the technical specifications of the electronic board, finding application in the various sectors of thermoregulation. We develop and produce custom electronic equipment and systems, collaborating with leading manufacturers of heating, air conditioning and appliances.

Production






Production is flexible and guaranteed by the most advanced technologies thanks to the use of THT and SMD assembly machines; all processing is monitored by X-Ray technology and is performed in full compliance with national and international regulations.

Testing



For each product functional tests and memory/micro programming are performed; for each project while needle bed machines are specially designed to perform circuit and mini-functional tests to guarantee the highest quality/reliability of the equipment and systems produced.





IMIT CONTROL SYSTEM S.R.L.

www.imit.it

Via Varallo Pombia, 19

28053 Castelletto Ticino (NO) - Italia

tel. +39 0331 941600 - fax +39 0331 973100

e-mail: info@imit.it

Rielaborazione grafica dell'opera "Omino Elettromeccanico IMIT" di Enrico Baj.
All rights reserved.

600061 Rev.0325